

付表7 ISC / NSK と他社製品との呼び番号対照表

Appendix Table7 Conversion

(1) メートル系 単列深溝玉軸受（開放形）

Deep groove ball bearings : Open type (Metric series)

軸径 Bore diameter (mm)	(inch)	ISC/NSK	NMB	NTN		
1	0.0394	681	L-310	681		
		MR31	L-310W51	—		
		691	R-410	691		
1.2	0.0472	MR41X	R-412	BC1.2-4		
1.5	0.0591	681X	L-415	68/1.5		
		691X	R-515	69/1.5		
		601X	R-615	60/1.5		
2	0.0787	682	L-520	682		
		MR52B	L-520W02	BC2-5		
		692	R-620	692		
		MR62	R-620W52	BC2-6		
		MR72	R-720Y52	BC2-7A		
		602	R-720	602		
2.5	0.0984	682X	L-625	68/2.5		
		692X	R-725	69/2.5		
		MR82X	R-825Y52	BC2.5-8		
3	0.1181	602X	R-825	60/2.5		
		MR63	L-630	673		
		683A	L-730	683		
3	0.1181	MR83	R-830Y52	BC3-8		
		693	R-830	693		
		MR93	R-930Y52	BC3-9		
		603	R-930	603		
		623	R-1030	623		
		633	—	633		
4	0.1575	MR74	L-740	674A		
		MR84	L-840	BC4-8		
		684A	L-940	684AX50		
		MR104B	L-1040X2	BC4-10		
		694	R-1140	694		
		604	R-1240	604		
4	0.1575	624	R-1340	624		
		634	R-1640	634		
		5	0.1969	MR85	L-850	675
		MR95	L-950	BC5-9		
		MR105	L-1050	BC5-10		
		685	L-1150	685		
5	0.1969	695	R-1350	695A		
		605	R-1450	605		
		625	R-1650	625		
		635	R-1950	635		

軸径 Bore diameter (mm)	(inch)	ISC/NSK	NMB	NTN		
6	0.2362	MR106	L-1060	676A		
		MR126	L-1260	BC6-12		
		684A	L-1360	686		
		696	R-1560X2	696		
		606	R-1760X2	606		
		626	R-1960	626		
6	0.2362	636	—	636		
		7	0.2756	MR117	L-1170	677
		MR137	L-1370	BC7-13		
		687	L-1470	687A		
		697	—	697		
		607B	R-1970	607		
7	0.2756	627	R-2270	627		
		637	—	637		
		8	0.3150	MR128	L-1280	678A
		MR148	L-1480	BC8-14		
		688A	L-1680	688A		
		698	R-1980	698		
8	0.3150	689	L-1790	689		
		9	0.3543	689	L-1790	689
ステンレス鋼の場合 In case of stainless steel		JIS型番は 基本番号の 後に“-H-” 694-H- 特殊寸法型番は 基本番号の 頭に“S” SMR117	DD	<input type="text"/>	F-	<input type="text"/>
例 Example			DDL-1170		F-677	

(2) メートル系 単列深溝玉軸受 (両シールド形) Deep groove ball bearings : Shielded type (Metric series)

軸径 Bore diameter (mm)	(inch)	ISC/NSK	NMB	NTN
1.5	0.0591	681XZZ	L-415X5ZZ	W68/1.5ZZA
		691XZZ	R-515ZZ	W69/1.5ZZA
		601	R-615ZZ	W60/1.5ZZA
2	0.0787	682ZZ	L-520ZZ	W682ZZA
		MR52BZZ	L-520ZZW52	WBC2-5ZZA
		692ZZ	R-620ZZ	W692ZZA
		MR62ZZ	R-620ZZY52	—
		MR72ZZ	R-720ZZY03	WBC2-7ZZA
		602ZZ	R-720ZZ	W602ZZA
2.5	0.0984	682XZZ	L-625ZZ	W68/2.5ZZA
		692XZZ	R-725ZZ	W69/2.5ZZA
		602XZZ	R-825ZZ	W60/2.5ZZA
3	0.1181	MR63ZZ	L-630ZZ	WA673ZZA
		683AZZ	L-730ZZ	W683ZZ
		693ZZ	R-830ZZ	W693ZZ
		MR93ZZ	R-930ZZY04	WBC3-9ZZA
		623ZZ	R-1030ZZ	623ZZ
4	0.1575	633ZZ	—	633ZZ
		MR74ZZ	L-740ZZ	WA674ZZA
		MR84ZZ	L-840ZZ	WBC4-8ZZ
		684AZZ	L-940ZZ	W684AX50ZZ
		MR104BZZ	L-1040X2ZZ	WBC4-10ZZ
		694ZZ	R-1140ZZ	694ZZ
		604ZZ	R-1240KK1	604ZZ
5	0.1969	624ZZ	R-1340HH	624ZZ
		634ZZ1	R-1640HH	634ZZ
		MR85ZZ	L-850ZZ	WA675ZZ
		MR95ZZ1	L-950ZZ	WBC5-9ZZ
		MR105ZZ	L-1050ZZ	WBC5-10ZZ
		685ZZ	L-1150ZZ	W685ZZ
		695ZZ	R-1350ZZ	695AZZ
		605ZZ	R-1450ZZ	605ZZ
6	0.2362	625ZZ1	R-1650HH	625ZZ
		635ZZ1	635ZZ	635ZZ

軸径 Bore diameter (mm)	(inch)	ISC/NSK	NMB	NTN
6	0.2362	MR106ZZ1	L-1060ZZ	WA676AZZ
		MR126ZZ	L-1260ZZ	WBC6-12ZZ
		686AZZ1	L-1360ZZ	W686ZZ
		696ZZ1	R-1560X13KK	696ZZ
		606ZZ	R-1760X2ZZ	606ZZ
		626ZZ1	R-1960ZZ	626ZZ
7	0.2756	636ZZ	—	636ZZ
		MR117ZZ	L-1170ZZ	WA677ZZ
		MR137ZZ	L-1370ZZ	WBC7-13ZZ
		687ZZ1	L-1470KK	W687AZZ
		697ZZ1	—	697ZZ
8	0.3150	607ZZ1	R-1970ZZ	607ZZ
		627ZZ	R-2270HH	627ZZ
		637ZZ	—	637ZZ
		MR128ZZ1	L-1280ZZ	W678AZZ
9	0.3543	MR148ZZ	L-1480ZZ	WBC8-14ZZ
		688AZZ1	L-1680ZZ	W688AZZ
		698ZZ	R-1980KK	698ZZ
		608ZZ	R-2280ZZ	608ZZ
ステンレス鋼の場合 In case of stainless steel 例 Example		689ZZ1	L-1790ZZ	W689ZZ
		JIS型番は基本番号の後ろに“-H-” 694ZZ-H- 特殊寸法型番は基本番号の頭に“-S” SMR117ZZ	DD <input type="text"/>	F- <input type="text"/>
			DDL-1170ZZ	F-WA677ZZ

(5) インチ系 単列深溝玉軸受（開放形）

Deep groove ball bearings : Open type (Inch series)

軸径 Bore diameter (mm)	(inch)	ISC/NSK	BARDEN	MPB	RMB	NMB	NTN
1.016	0.0400	R09	—	2C	UL1304	RI-2X2	R01
1.191	0.0469	R0	R0	25C	UL1505	RI-2 $\frac{1}{2}$	R0
1.397	0.0550	R1	R1	3C	R1706	RI-3	R1
1.984	0.0781	R1-4	R1-4	4C	R2508	RI-4	R1-4
2.380	0.0937	R133	R133	3332C	UL3006	RI-3332	R133
		R1-5	R1-5	5C	R3010	RI-5	R1-5
3.175	0.1250	R144	R144	418C	UL4008	RI-418	R144
		R2-5	R2-5	518C	R4010	RI-518	R2-5
		R2-6	R2-6	618C	—	RI-618	RA2-6
		R2	R2	R2C	R4012	R-2	R2
		R2A	R2A	R2AC	—	—	RA2
3.967	0.1562	R155	R155	5532C	UL5010	RI-5532	RA155
4.762	0.1875	R156	R156	5632C	UL6010	RI-5632	R156
		R166	R166	6316C	UL6012	RI-6632	R166
		R3	R3	R3C	R6016	R-3	R3
6.350	0.2500	R168BZZ	R168	614C	UL8012	RI-614	R168A
		R188	R188	814C	UL8016	RI-814	R188
		R4B	R4	R4C	R8020	R-4	R4
		R4AA	R4A	R4AR	—	RI-1214	—
7.938	0.3125	R1810	R1810	8516C	—	RI-8516	—
ステンレス鋼の場合 In case of stainless steel 例 Example		特殊寸法型番は 基本番号の頭に“S” SR166	S <input type="text"/> SR166	S <input type="text"/> S6316C	<input type="text"/> X UL6012X	DD <input type="text"/> DDRI-6632	F- <input type="text"/> F-R166

(6) インチ系 単列深溝玉軸受（両シールド形）

Deep groove ball bearings : Shielded type (Inch series)

軸径 Bore diameter (mm)	(inch)	ISC/NSK	BARDEN	MPB	RMB	NMB	NTN
1.191	0.0469	R0ZZ	R0SS	25CHH	ULZ1505	RI-2 $\frac{1}{2}$ ZZ	RA0ZZA
1.397	0.0550	R1ZZ	R1SS	3CHH	RX1706	RI-3ZZ	RA1ZZA
1.984	0.0781	R1-4ZZ	R1-4SS	4CHH	RX2508	RI-4ZZ	RA1-4ZZA
2.380	0.0937	R133ZZS	R133SS	3332CHH	ULZ3006	RI-3332ZZ	RA133ZZA
		R1-5ZZ	R1-5SS	5CHH	RX3010	RI-5ZZ	RA1-5ZZA
3.175	0.1250	R144ZZ	R144SS	418CHH	ULZ4008	RI-418ZZ	RA144ZZA
		R2-5ZZ	R2-5SS	518CHH	RX4010	RI-518ZZ	RA2-5ZZ
		R2-6ZZ	R2-6SS	618CHH	—	RI-618ZZ	RA2-6ZZA
		R2ZZ	R2SS	R2CHH	RX4012	R-2ZZ	RA2ZZA
		R2AZZ	R2ASS	R2ACHH	—	—	RA2ZZ
3.967	0.1562	R155ZZ	R155SS	5532CHH	ULZ5010	RI-5532ZZ	RA155ZZA
4.762	0.1875	R156ZZ	R156SS	5632CHH	ULZ6010	RI-5632ZZ	RA156ZZ
		R166ZZ	R166SS	6316CHH	ULZ6012	RI-6632ZZ	RA166ZZ
		R3ZZ	R3SS	R3CHH	RX6016	R-3HH	RA3ZZ
6.350	0.2500	R168BZZS	R168SS	614CHH	ULZ8012	RI-614ZZ	R168AZZ
		R188ZZ	R188SS	814CHH	ULZ8016	RI-814ZZ	RA188ZZA
		R4BZZ	R4SS	R4CHH	RX8020	R-4KK	R4ZZ
		R4AAZZ	R4ASS	R4ARHH	—	RI-1214ZZ	RA4ZZ
7.938	0.3125	R1810ZZ	R1810SS	8516CHH	—	RI-8516ZZ	—
ステンレス鋼の場合 In case of stainless steel 例 Example		特殊寸法型番は 基本番号の頭に“S” SR166ZZ	S <input type="text"/> SR166SS	S <input type="text"/> S6316CHH	<input type="text"/> X ULZ6012X	DD <input type="text"/> DDRI-6632ZZ	F- <input type="text"/> F-RA166ZZ